Rapid Freeze Moderate Ambient Air Cooled

Condensing Units

COOL SOLUTIONS SINCE 1912

HOWE Proven. Best Choice.

Howe's moderate ambient condensing units are sized and configured to match Howe Rapid Freeze ice flakers. These units are designed for unexcelled quality, reliability, and long life. They are durable, energy efficient and they provide a high degree of flexibility to a wide diversity of industrial applications.

STANDARD FEATURES

- High efficiency Copeland semihermetic compressors with POE Oil.
- Electrical controls in weatherproof control box with compressor contactor and fused control circuit.
- Head pressure control system
- Suction & liquid vibration eliminators.
- Liquid line filter-drier and sight glass.

SPECIAL FEATURES

- Pump down toggle switch
- Suction Accumulator
- Oil Separator with oil return line.
- Separate high pressure, low pressure control switches

OPTIONAL FEATURES

- Coated condenser coils for harsh environments.
- Oversized condensing units rated for 110°F ambient conditions.



APPLICATIONS

- Produce Harvesters
- Produce Wholesalers
- Produce Markets
- Industrial Bakeries
- Seafood Processors
- Seafood Distributors
- Meat Processors
- Sausage Processors
- Poultry Processors
- Concrete Cooling
- Amusement Parks
- Industrial Catering


Moderate Ambient

AC Condensing Units

ТОР









CONDENSING UNIT

| MODEL | DIME IN H | NSIONS W | | CM H | | | CONNECTION | ON SIZES LIQUID | REQUIRED Line Sizes SUCTION | RUN (ODS) LIQUID | REC CAP LBS | SHIPPIN | NG WEIGHT KG | |
|-----------------|-----------------|-------------|---------|---------|-----|-----|------------|--------------------|-----------------------------------|------------------------|-------------------|---------|-----------------|--|
| MA77-A-R404A-* | 55 | 44-3/4 | 167-3/8 | 140 | 114 | 424 | 21/8 | 1-1/8 | 21/8 | 7/8 | 124 | 2200 | 998 | |
| MA77-A-R404A-2 | 55 | 44-3/4 | 167-3/8 | 140 | 114 | 424 | 21/8 | 1-1/8 | 21/8 | 7/8 | 124 | 2510 | 1140 | |
| MA102-A-R404A-* | 55 | 44-3/4 | 167-3/8 | 140 | 114 | 424 | 21/8 | 7/8 | 25/8 | 11/8 | 157 | 2290 | 1040 | |

^{*= 1} for 230/3/60, 3 for 460/3/60, 4 for 575/3/60

ELECTRICAL R-404A

| VOLTAGE | MODEL | COMPRESS(| OR LRA | COND | | N MOTORS FLA (EACH) | UNIT AMPS | MCA | МОР |
|--------------|--|--------------|---------------------------|-------|--------------|------------------------|---------------|----------------|------------|
| 208-230/3/60 | MA77-A-R404A-1 MA102-A-R404A-1 | 80.7 95.6 | 450 470 | 2 2 | 3700 3700 | 6.6 6.6 | 93.9 108.8 | 11415 132.7 | 175 225 |
| 460/3/60 | MA77-A-R404A-3 MA102-A-R404A-3 | 40.4 47.8 | 225 235 | 2 2 | 3700 3700 | 3.1 3.1 | 46.6 54 | 56.7 65.9 | 90 110 |
| 575/3/60 | MA77-A-R404A-4 MA102-A-R404A-4 | 32.5 39.6 | 172 200 | 2 2 | 3700 3700 | 2.5 2.5 | 37.5 44.6 | 45.6 54.5 | 70 90 |
| 380/3/50 | MA77-A-R404A-2 MA102-A-R404A-2 | 40.4 | 225 | 2 | 3700 | 3.1 | 46.6 | 56.7 | 90 |
| | IS are same as 101-RHS. 102- vided with Howe furnished co | | parate refrigeration circ | uits. | | | | | |

